

WÖHLER

TECHNOLOGY FOR PROFESSIONALS

MEASURE | INSPECT | CLEAN

Made in Germany

YOUR WÖHLER TEAM IN THE UK



WOHLER UK LIMITED
G1 Lincoln House
Lincoln Way
Sherburn in Elmet
LS25 6PJ

☎ 01977 80 60 40
✉ info@wohler.co.uk
🌐 www.wohler.co.uk

Monday to Friday
9 am – 5 pm



Andrew Moore
Managing Director



Ann Booker
Office Manager



Hold the camera of your smartphone over the QR code to be scanned and scan it. Once the code has been read, the relevant product is automatically called up on the Wöhler homepage. Now all you have to do is add it to your shopping basket and order.

Measuring

Wöhler A 450/ 450 L Flue Gas Analyser..... P. 4 – 5
Wöhler A 550/ 550 L Flue Gas Analyser..... P. 6 – 8
Wöhler TI 410 Dew Point Indicator P. 9
Wöhler DP 600 Leakage Tester P. 10 – 13
Wöhler M 603 Leakage Tester..... P. 14 – 15
Wöhler SC 660 Smart Connect P. 16 – 17
Wöhler SC 602 Smart Connect P. 18 – 19
Wöhler DM 602 Digital Manometer..... P. 20 – 21
Wöhler GS 220 Gas Sniffer..... P. 22
Wöhler GS 300 Gas Sniffer..... P. 23
Wöhler RL 200 Refrigerant Leak Detector P. 24
Wöhler RL 300 Refrigerant Leak Detector P. 25
Wöhler MR 400 Refrigerant Manifold..... P. 26
Wöhler RS 400 Refrigerant Scale P. 27
Wöhler DC 410^{FLOW} P. 28 – 29
Wöhler FA 410 Fan Anemometer..... P. 30 – 31
Wöhler IR Temp 310 Infrared Thermometer..... P. 32 – 33
Wöhler CDL 210 CO₂ Datalogger P. 34
Wöhler IQ 300 CO₂ Meter..... P. 35
Wöhler CM 220 Carbon Monoxide Meter P. 36
Wöhler KM 410 IAQ Instrument P. 37

Visual Inspection

Wöhler VIS 500 Visual Inspection System..... P. 38 – 39
Wöhler VIS 700 HD Visual Inspection System..... P. 40 – 41
Wöhler VE 220 HD Video Endoscope..... P. 42
Wöhler VE 400 HD Video Endoscope..... P. 43
Wöhler VE 500 HD Video Endoscope..... P. 44 – 46

Cleaning of waste water pipes

Wöhler RM 200 Drain Cleaning Machine..... P. 48 – 49
Wöhler RM 300 Drain Cleaning Machine..... P. 50 – 51
Wöhler RM 400 Drain Cleaning Machine..... P. 52 – 53

Cleaning Technology

Wöhler Snap & Sweep® System..... P. 54 – 55
Wöhler Rotary Viper Duct M5 P. 56
Wöhler Rotary Viper Duct M10..... P. 57
Wöhler Viper S..... P. 58
Wöhler Viper M PLUS P. 59
Accessories Cleaning Technology..... P. 60 – 63
SF 300 Dust Collector P. 64 – 65
Wöhler Compressed Air Cleaning..... P. 66 – 67



Wöhler A 450 L Flue Gas Analyser

Maintenance / adjustment work / flue gas measurement



Features

- Switch on – read off – done
- Rugged and compact analyser that offers all measurement and tuning functions
- High-resolution 5" colour touchscreen: 14 measured values available at a glance
- Future-proof network connectivity with Wireless LAN
- Wöhler Flue Gas Analysis App included for Android and iOS
- Low follow-up costs: 48-month device and sensor guarantee¹⁾ without maintenance conditions

Technical Data

Display	5" colour touchscreen
Sensors	up to 3
	O ₂ 0...21 %
	CO 0...5,000 ppm
	0...100,000 ppm
	NO 0...3,000 ppm (optional)
Power supply	Lithium-ion battery 6 h service life
Weight	620 g (with NO sensor included)
Safety	3 Filter technology with filter monitoring

Wöhler A 450 L

5,000 ppm CO-Sensor

Scope of delivery: Wöhler A 450 L with 5,000 ppm CO-Sensor, WiFi, USB and IR interface, probe 250 mm with 1.5 m hose, USB charger with micro USB cable, Li-ion battery 3.6 V / 2250 mAh, 25 cotton filters

Article no. 4503

Optional with 3,000 ppm NO-Sensor Article no. 4703



Wöhler A 450 L










100,000 ppm CO-Sensor

Scope of delivery: Wöhler A 450 L, 100,000 ppm CO-Sensor, WiFi, USB and IR interface, probe 250 mm with 1.5 m hose, USB charger with micro USB cable, Li-ion battery 3.6 V / 2250 mAh, 25 cotton filters

Article no. 4672

Optional with 3,000 ppm NO-Sensor Article no. 4979

Accessories-Sets	Article no.
 Starter Kit Maintenance Tasks Plastic case MIDI Wöhler A 450 L, Clamping cone, Water stop filters, 3 pieces, Cotton filters, 25 pieces, Wöhler TD 100 Thermal Fast Printer	6596
 Comfort Set Maintenance Tasks Plastic case Maxi Wöhler A 450, Air temperatur probe 220 mm, Clamping cone, PTFE cone, Water stop filters, 3 pieces, Cotton filters, 25 pieces, the Pressure Measurement Set, Wöhler TD 100 Thermal Fast Printer	6597

Accessories	Article no.
 Plastic Case MIDI 45 x 42 x 14 cm	6594
 Plastic Case MAXI 44.5 x 51.5 x 18 cm	4704
 Backpack for Wöhler A 450 / A 550	5101
 Wöhler TD 100 Thermal Fast Printer Infrared printer with 1 roll thermal paper	4160
 Air Temperature Probe 220 mm for Wöhler A 450 / A 550 with 1.8 m Cable	6545
 Probe 250 mm with 1.5 m hose for A 450 L	4498
 Clamping Cone for probes Ø 8 mm stainless steel, to stabilise the gas probe in the flue pipe	2494
 Threaded cone for probes Ø 8 mm stainless steel, to stabilise the gas probe in the flue pipe	1235
 PTFE Cone for air temp. probes Ø 8 mm to stabilise air temperature probes in openings Ø 10 - 15 mm	2463

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/164



Wöhler Flue Gas Analysis App

Send and process all measurement data from the Wöhler Flue Gas Analysis via WiFi to mobile devices using the app.

1) Thermocouples, rechargeable batteries and NO sensors are excluded. Please refer to our general terms and conditions for further information.

Wöhler A 550/ 550 L Flue Gas Analyser

Maintenance / adjustment work / flue gas measurement



Features

- Overview: Large 7" touch display with visualisation of 14 measured and calculated value
- Convenient: Switch on – Read off – Done
- Safety: The CO purge pump actively protects the H₂-compensated CO sensor from overload
- Low follow-up costs: 48-month device and sensor guarantee¹⁾ without maintenance conditions
- Equipped for the future: Accessories for special applications, e.g. measurements on combined heat and power plants
- All-round device: Slots for 5 sensors
- Fast: Fresh air pump for simultaneous calibration and core flow search

Technical Data

Display	7"	
Sensors	up to 5	
	O ₂	0...21 %
	CO	0...35,000 ppm 0...100,000 ppm
	NO	0...3,000 ppm (optional)
	NO ₂	0...1,000 ppm (optional)
Power supply	Lithium-ion rechargeable battery, 12 hr service life	
Weight	from 1,250 g	
Safety	5 filter technology with filter monitoring	

Wöhler A 550 Flue Gas Analyser
4,000 ppm CO-Sensor

Scope of delivery: Wöhler A 550 Flue Gas Analyser with Bluetooth-, USB- and IR-interface, O₂ sensor, CO sensor 4,000 ppm, CO protection pump, cable hose 1.7 m, changeable gas probe 295 mm, combustion air temp. plug, USB-charger with Micro-USB cable, Lithium-ion rechargeable battery, 1 waterstop filter, 1 coarse filter, 25 wadding filters, plastic case

Article no. 8150



















Optional with 3,000 ppm NO-Sensor Article no. 8153

Wöhler A 550 L Flue Gas Analyser
35,000 ppm CO-Sensor

Scope of delivery: Wöhler A 550 L Flue Gas Analyser with O₂ + CO 35,000 ppm, cable hose 1.7 m, gas probe 275 mm, USB-charger with Micro-USB cable, Lithium-ion rechargeable battery, 1 waterstop filter, 1 coarse filter, 25 wadding filters, plastic case

Article no. 8133

Optional with 3,000 ppm NO-Sensor Article no. 8148

Accessories		Article no.
	Kit Maintenance Tasks Air Temperature Probe 220 mm, PTFE Cone for air temperature probes Ø 8 mm to stabilise air temperature probes in openings Ø 10 – 15 mm, Wöhler TD 100 Thermal Fast Printer, 10 rolls Thermal Paper for Wöhler TD 100 Thermal Fast Printer, Servicebag incl. 1 water stop filter, 1 coarse filter, 25 wadding filters, silicone grease (6 g), various o-rings	11373
	Plastic Case MAXI Very robust case with foam inlet, ideal for the daily use. Provides enough room for the Wöhler A 550 flue gas analyser, as well as the thermo printer TD 100, soot pump kit, probes and cones	5577
	Wöhler A 550 Aluminium Framed Case Stable & upright including three horizontal inner compartments, document pocket, probe holding loops in the lid	3315
	Backpack for Wöhler A 450 / A 550	5101
	Wöhler TD 100 Thermal Fast Printer Infrared printer with 1 roll thermal paper	4160
	Air Temperature Probe 220 mm for Wöhler A 450 / A 550 with 1.8 m Cable	6545
	Hose assembly Wöhler A 550 L Twin hose model, 275 mm	7126
	Clamping Cone for probes Ø 8 mm stainless steel, to stabilise the gas probe in the flue pipe	2494
	Threaded Cone for probes Ø 8 mm stainless steel, to stabilise the gas probe in the flue pipe	1235
	PTFE Cone for air temp. probes Ø 8 mm to stabilise air temperature probes in openings Ø 10 - 15 mm	2463
	Hose Assembly 3.0 m for Wöhler A 550 Gas Probe 3m cable without plug-in probe, programmed and calibrated, with coarse filter	7179
	Gas Probe With union nut and protective cap 500 mm	9614
	295 mm	9622
	180 mm	9613
	130 mm	9652
	Wöhler A 450 / 550 Flexible Probe 300 mm long, TÜV test, BS EN 50379 Part 2	3242
	Dew Point Indicator Probe for Wöhler A 550	5512
	Wood Moisture Probe for Wöhler A 550	5513














Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_127



¹⁾ Thermocouples, rechargeable batteries and NO sensors are excluded. Please refer to our general terms and conditions for further information.

Accessories		Article no.
	Thermal Paper 10 rolls, for Thermal Printer Wöhler TD 100 – 12 m long/ roll,	4145
	Service Bag for Wöhler A 450/ A 550 L 1 water stop filter, 1 coarse filter, 25 wadding filters, silicone grease (6 g), various o-rings	4734
	Service Bag for Wöhler A 550/ A 550 L 1 water stop filter, 1 coarse filter, 25 wadding filters, silicone grease (6 g), various o-rings	4733
	Water Stop Filters for Wöhler A 450 / A 550 pack with 3 pieces	9621
	Coarse Filters for Wöhler A 450 / A 550 pack with 5 pieces	9632
	Wadding Filters pack with 25 pieces	4286
	pack with 150 pieces	4288
	Charger for Wöhler A 550 / A 450 / L 200	5502
	PC-Software Wöhler A 450 Languages EN / FR / IT / CZ / NL / CN for online measurements, diagram functions and export to MS Excel	4499
	PC-Software Wöhler A 550 Languages EN / FR / IT / CZ for online measurements, diagram functions and export to MS Excel	4428
	Wöhler Flue Gas Analysis App Available for both Android and iOS devices! The Wöhler Flue Gas Analysis App is precisely what you need for your measuring and adjustment tasks.	 

Sensors field replaceable		Article no.
O ₂ -Sensor	0...21 Vol. %	5594
CO-Sensor	4,000 ppm	8166
CO-Sensor	4,000 ppm H ₂ compensated	5595
CO-Sensor	35,000 ppm	4496
CO _H -Sensor	100,000 ppm	5596
NO-Sensor	3,000 ppm	5597

Wöhler TI 410 Dew Point Indicator

Control of flue gas back pressure on room-sealed gas fireplaces

Features

- Control of flue gas back pressure on fireplaces
- Visual and acoustic signal in the event of flue gas backflow
- Sensitivity adjustable in four stages to adapt to different ambient conditions
- Automatic switch-off after four minutes, therefore long battery life
- High level of safety due to:
 - Pulsed alarm tone
 - Visual bar graph display
 - Ambient temperature measurement

Technical Data

Temperature measuring range	-40...100 °C
Sensor plate	Double-sided
Indicators	acoustic through pulsed alarm tone
	optical through four-step bar
	increased temperature indication relative to the surroundings



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

[wohler.co.uk/P_137](https://www.wohler.co.uk/P_137)



Wöhler TI 410 Dew Point Indicator

Scope of delivery: Wöhler TI 410 Dew Point Indicator with swan neck, batteries and flexarm for sensor plate

Article no. 6808

Wöhler DP 600 Leakage Tester

for tightness testing of chimneys and flue gas systems and for 4 Pa test



Features

- Equipped with a brilliant colour display and a simple menu navigation
- Volume flow adjustable up to 200 m³/h
- Extended pressure range up to ±7,000 Pa
- Integrated memory for up to 100 measurement records
- USB interface for the PC
- IrDA interface for the printer
- Tightness classes preset for flue gas systems N, P and H according to EN 1443
- 4 / 8 Pa test without any auxiliary measuring instrument

Technical Data

Pressure	Measuring range	±7,000 Pa
	Resolution	0.1 Pa from 0...900 Pa 1 Pa starting from 900 Pa
	Accuracy	±0.5 Pa ±2.5 % from measured value
Air volume flow without adapter	Measuring range	0...200 Nm/h
	Resolution	0.1 Nm/h
	Accuracy	±2.5 Nm/h ±5 % from measured value
Air volume flow with adapter 3.0	Measuring range	0...10 Nm/h
	Resolution	0.01 Nm/h
	Accuracy	±0.05 Nm/h ±5 % from measured value
Air volume flow with adapter 0.3	Measuring range	0...18 NL/min
	Resolution	0.01 NL/min
	Accuracy	±0.05 NL/min ±5% from measured value

Wöhler DP 600 Leakage Tester

Tightness testing of chimneys and flue gas

Scope of delivery: Wöhler DP 600, mains cable EU plug, adapters for all tightness tests of flue gas systems, plastic case, comes without sealing bladders and elements

Article no. 2678

Sets		Article no.
	Sealing Set Compact for P/M/H Test for 200/ 1,500/ 5,000 Pa measurements Sealing Bladder Compact Ø 40 - 150 mm with gas lead-through, Sealing Bladder Compact Ø 40 - 150 mm without gas lead-through, with connection for Telescopic Set Sealing Bladder, Telescopic Set Sealing Bladder Compact Ø 40 - 150 mm, consisting of extension hoses set 1 x 2.5 m / 1 x 5 m / 1 x 10 m and connectors for GRP rods with thread M5, Threaded adapter M5 to M10 for GRP rods with M10 thread, aluminium pressure pump	6578
	Sealing Bladder Compact Ø 40 - 150 mm without gas lead-through with telescopic set, for Wöhler DP 600 Sealing Bladder Compact Ø 40 - 150 mm without gas lead-through, with connection for Telescopic Set Sealing Bladder, Telescopic Set Sealing Bladder Compact Ø 40 - 150 mm consisting of extension hoses set incl. extension hoses 1 x 2.5 m / 1 x 5 m / 1 x 10 m and connectors for GRP rods with thread M5, Threaded adapter M5 to M10 for GRP rods with M10 thread, aluminium pressure pump	6795
	Telescope Set Sealing Bladder Compact Ø 40 - 150, for Wöhler DP 600 Extension hose set incl. extension hoses 1 x 2.5 m / 1 x 5 m / 1 x 10 m, Connector for GRP rods with thread M5, Threaded adapter M5 to M10 for GRP rods with M10 thread	6567
	Sealing Set Type N for Wöhler DP 600, for 20+40 Pa-measurements Probe Wöhler DP 600 / 23, Extension pipe, Ferrule, Pressure hose 4 m, Air hose 3.75 m, Several foam sealing elements incl. #11078, #11059, #11066, #11001, #11000	11140
	4/8 Pa-Test-Set DP 600 (detailed procedure) Extension hose, hose capillary set with minus (-) connection and plus (+) connection, round sealing elements with 11-20 cm hole, XXL transport case	11149
	Leakage Test Kit Wöhler DP 600 for stoves Sealing elements, extension tube 3.75 m, flexible capillary 6 m minus (-) and connectors, flexible capillary 6m plus (+) and connectors, aluminium case XXL	2677




Accessories		Article no.
	Push Rod Wöhler sealing bladder compact D40 - D150	11186
	Wöhler Viper S 15 m GRP Rod 4.5 mm, 15 m stainless steel end piece M5, guidance adapter (without stars)	2028
	Capillary Hose with (+) Connector Wöhler DP 600 / 700 for 4 Pa-Test capillary hose 6 m, connector, silicone hose	2604
	Capillary Hose with (-) Connector Wöhler DP 600 / 700 for 4 Pa test Capillary hose 6 m and silicone hose	2672
	Sealing Bladder Compact Ø 40 - 150 mm with gas lead through for Wöhler DP 600 with connecting hoses for air and pressure	6566
	Sealing Bladder Compact Ø 40 - 150 mm without gas lead through, for Wöhler DP 600 with connection for Telescope Set Sealing Bladder and hose with shut-off valve	6560
	Gas coupling Ø 15 x 31 mm POM black for Wöhler DP 600 / DP 700; D 6.5, for the retrofitting of Wöhler DP 23 / 94 hose system	4732
	Sealing Bladder with gas lead through, for Wöhler DP 600 / DP 23 Ø 150 - 350 mm	7974
	Sealing Bladder without gas lead through, for Wöhler DP 600 / DP 23 Ø 150 - 350 mm	7966
	Sealing Bladder without gas lead through, for Wöhler DP 600 / DP 23 Ø 150 - 350 mm	7971
	Sealing Bladder without gas lead through, for Wöhler DP 600 / DP 23 Ø 150 - 350 mm	7981
	Wöhler Telescopic Bladder Ø 150 - 350 mm for Wöhler DP 600 / DP 23 without gas feed-through, with 20 m hose for pushing upwards, mounting for GRP rod or viper	7938

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_122

Accessories		Article no.
	Wöhler Replacement Bladder Body for compact bladders Ø 40 - 150	6794
 	Replacement Bladder for sealing bladders with or without gas lead through Ø 50 - 150 mm	8034
	Ø 150 - 350 mm	6217
	Ø 350 - 600 mm	6215
	Aluminium Pump Master-Blaster for test sets, gas pipes and sealing bubbles	53817
	Valve Set for compressor "Airman" and aluminium pump Master-Blaster	55447
	Extension Tube 3.75 m for Wöhler DP 600 Ø 50 mm	50676
	Measuring Hose Ø 5.5 mm / 1 m	2338
	Filter pad Wöhler for Wöhler DP 600 / DP 700 5 pieces	2617
	Smoke Cartridges pack of 5 for checking the tightness of flue gas systems each cartridge produces 3 - 4 minutes of light grey smoke	1795
	Sealing Element Round for measuring tasks for Wöhler DP 600 / 23 with hole Ø 4 cm Height 14 cm	
	Ø 11 - 15 cm	11055
	Ø 11 - 20 cm	11000
	Ø 14 -18 cm	11064
	Ø 17 - 21 cm	11054
	Sealing Element Round no hole for measuring tasks Wöhler DP 600 / 23 Height 14 cm	
	Ø 11 - 15 cm	11056
	Ø 14 - 18 cm	11066
	Ø 17 - 21 cm	11057
	Ø 23 - 27 cm	11058
	Sealing Element Square with hole for measuring tasks Wöhler DP 600 / 23 Height 14 cm Hole Ø 4 cm 10 x 20 cm 15 x 26 cm	11069
	11 x 23 cm 19 x 31 cm	11059
	12 x 12 cm 19 x 19 cm	11070
	22 x 25 cm 29 x 31 cm	11074
	22 x 33 cm 35 x 40 cm	11072
	27 x 41 cm 34 x 48 cm	11075

Accessories		Article no.
	Sealing Element Square no hole for measuring tasks for Wöhler DP 600 / 23 Height 14 cm 8 x 16 cm 16 x 26 cm	11077
	12 x 12 cm 21 x 21 cm	11001
	12 x 24 cm 20 x 32 cm	11078
	18 x 18 cm 23 x 23 cm	11060
	22 x 22 cm 29 x 29 cm	11071
	27 x 27 cm 34 x 34 cm	11065
	33 x 33 cm 39 x 39 cm	11073
	100 x 100 cm	11076
	Aluminium Case XXL 48 x 27 x 48 cm	5824
	Universal Box for Wöhler DP 600 / DP 700 offers sufficient space for the Wöher DP 600 / DP 700 leakage tester as well as printer, sealing set type N and all sealing elements (remove original insert)	50784

Measuring Knowledge platform

Leakage testing of exhaust gas systems

To keep the heating system running smoothly, it's essential to use fans or blowers to expel flue gases outdoors. This process generates an overpressure in the flue gas system. If there are any leaks in the flue gas pipes, harmful gases could seep into the indoor air. For this reason, it's a good idea to perform a leak test on the flue gas system.

Scan now!



Wöhler M 603 Leakage Tester

Load/tightness/serviceability test



Features

- Measurements on gas pipes and components
 - Load, leak and serviceability test
 - Gas regulator testing
- Measurements on drinking water pipes in accordance with BS EN 806
 - with air
 - with water in conjunction with the Wöhler SC 660 Smart Connect
- Logger measurements
- Many pressure and temperature measurements (also possible via external temperature sensor)
- Intuitive operation via the robust 5" colour touchscreen
- All pressure tests on gas and drinking water pipes
- Guaranteed standard-compliant measurement thanks to automatic measurement sequence with built-in pumps
- Extensive range of accessories for all pressure tests



Technical Data
















Differential pressure measurement (temperature-compensated piezo bridge)	Measuring range	±3,000 hPa
	Accuracy	< 3% of the measured value; in the range < ± 2 hPa better than ± 0.06 hPa
	Resolution	0.01 hPa in the range from – 210 hPa to +210 hPa, otherwise 0.1 hPa
Leakage amount (usability measurement)	Measuring range	0.0 l/h to 10.0 l/h, tested up to 8 l/h
	Accuracy	± 0.2 l/h in the range from 0 to 4 l/h, otherwise 5% of the measured value
	Resolution	0.1 l/h
Logger function	Scope	9,999 measurements
	Selectable scanning intervals	1 second to 24 h

Wöhler M 603 Leakage Tester

Scope of delivery: Wöhler M 603 Leakage Tester, Lithium-ion battery, Hand strap, Measuring tube 1.5 m, Power supply with USB cable

Article no. 11377

Accessories Sets	Article no.
 Comfort-Set Gas Tightness check set for gas pipes, Single tube meter cap DN 32, Plastic case M 6xx MAXI, High pressure stage cap G1/2 G1 MS SW42, High pressure stage cap G3/8 G3/4 MS SW36, 2x high pressure plugs 1 1/4", Flex-adapter for measurements at gas regulators, Pressure nozzle set	12114
 Professional-Set Gas Tightness check set for gas pipes, Single tube meter cap, High pressure plug G1 1/4 (2 pieces), Plastic case MAXI, High pressure stage plug G1/2 G1, High pressure stage plug G3/8 G3/4, Wöhler GS 300 Gas Sniffle, Wöhler TD 100 printer, Pressure nozzle set, Flex-adapter for gas regulators, Gas bladder, Wöhler M-series PC-software, Plastic case MIDI	12113

Accessories	Article no.
 Pressure Measurement Set for Wöhler Digital Manometer One 1.5 m measuring hose Ø 7.5 mm / Ø 3.5 mm each, plastic T-pieces 4 and 8 mm, plastic connector 4 mm, plastic reducer 4 to 8 mm	56126
 Wöhler Gas Pipe Tightness Set Valve block with 4 connection hoses (length 1m), with fast connection each, 2 conical closing plugs, Single closure, Pressure pump	10063
 Adapter Gas Counter DN 32 with connector maxi	21574
 High Pressure Plug 1/2" and 1" with gasket rings	7213
 High Pressure Plug 3/8" & 3/4" with gasket rings	7214
 High Pressure Plug 1 1/4" with plug nipple Maxi for two-pipe gas meter 2 pack	11023
 High Pressure lock 1/8"	21612
 Flex-Adapter G1/8" for measurements at gas regulators	11144
 Gas Bladder for Wöhler M 603 or DC 420 Gas bladder with self-locked coupler for measuring the leakage rate with gas	9232
 Wöhler M-Series PC-Software Languages: EN / IT / NL For analysing the measurement data of the Wöhler M 603 Leakage Tester. The software is available for download. You will receive a separate e-mail with the download link.	25009
 Plastic Case M 6xx MAXI Gas	11141
 Plastic Case M 6xx MIDI Gas	11146
 Service Bag for Wöhler DC 420 Silicon grease, Wadding filters, O-ring, Smart Plug	9243
 Wöhler TD 100 Thermal Fast Printer Infrared printer with 1 roll thermal paper	4160
 Thermal Paper 10 rolls for Thermal Printer Wöhler TD 100 - 12 m long/ roll,	4145



Wöhler M-Serie PC-Software

Transfer all measurement data from the Wöhler M 603 to the PC and analyse it there.

Wöhler SC 660 Smart Connect

Leak testing of drinking water pipes according to BS EN 806





Features

- Measurements of drinking water pipes with water according to BS EN 806
- Temperature measurements (internal and via external temperature sensors possible)
- High measuring range up to 60 bar
- Can be used as an independent measuring device with its own display
- Connection to the Wöhler Smart Connect App also enables live measurements, logger measurements and measurements in accordance with BS EN 806-4
- Pressure, temperature, relative humidity and ambient pressure
- Suitable adapters for e.g. tap, angle valve, wall disc, shower hose and aerator

Technical Data

Relative pressure (differential pressure compared to the ambient pressure)	Measuring range	-1...60 bar
	Permissible overload	65 bar
	Accuracy	< 3 % of measured value, in the range +/- 1 bar better than 0.03 bar
	Resolution	0.01 bar
Temperature, internal	Measuring range	-20...60 °C
	Accuracy	< ±1 °C
	Resolution	0.1 °C
Temperature, external	Measuring range	-20...800 °C
	Accuracy	-20...67 °C
	Resolution	0.1 °C

Accessories Sets	Article no.
 Comfort-Set Drinking Water Scope of delivery: Plastic case MIDI, Angle adapter 1/4" SAE 90°, High pressure lock G1/2 AG 1/4" SAE wall plate, Measurement adapter G3/4 IG 1/4" SAE tap, Measurement adapter G3/8 IG 1/4" SAE angle valve, Measurement adapter M 24 AG 1/4" SAE aerator, Measurement adapter M 22 IG 1/4" SAE shower hose, Clamp temperature probe Type K	10096
 Plastic Case MIDI Inner dimensions: 379 x 234 x 100 mm with nap foam	7278

Accessories	Article no.
 Angle Adapter 1/4" SAE 90° for Wöhler SC 660	8841
 High Pressure Lock G1/2 AG 1/4" SAE for Wöhler SC 660 Wall plate	8843
 Adapter G3/4 IG 1/4" SAE for Wöhler SC 660 Tap	8856
 Adapter G3/8 IG 1/4" SAE for Wöhler SC 660 Angle valve	8857
 Adapter M22x1 IG 1/4" SAE for Wöhler SC 660 Shower hose	11178
 Adapter M24x1 AG 1/4" SAE for Wöhler SC 660 Aerator	11179
 Clamp Temperature Sensor Type K 1.5m cable	62616
 Battery for SC 6xx and DM 602 Li-polymer battery module with USB-C charging port	8839
 Connection Valve 1/4"SAE IG, 1/4"SAE AG for Wöhler SC 660	62694

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_182



Wöhler SC 660 Smart Connect EN

Scope of delivery: Wöhler SC 660 Smart Connect, Batteries, Hand loop, Bag

Article no. 10133



Wöhler Smart Connect App

Send and process all measurement data from the Wöhler Smart Connect via Bluetooth® to mobile devices using the app.

Wöhler SC 602 Smart Connect

Load/tightness/serviceability test



Features

- Extremely responsive display of the measured value
- Illuminated display for quick reading of the measured value
- Settings, measurements and documentation made easy via thee Wöhler Smart Connect App
- Robust sensor up to 3,000 hPa and high-resolution measuring range (0.01 hPa)
- Integrated magnets, shock-protected housing
- Stable measured values in any position thanks to high-quality pressure sensor
- Optional: Lithium-polymer battery for an extra long service life
- Optimally equipped: Comprehensive accessories for all pressure tests

Technical Data

Differential pressure	Measurement range	±3,000 hPa
	Accuracy	< 3 % of measured value in the range < ±2 hPa better than ±0.06 hPa
	Resolution:	0.01 hPa in the range -210...210 hPa otherwise 0.1 hPa
Internal temperature measurement	Measurement range	-20...60 °C
External temperature measurement	Measurement range	-20...800 °C



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_181



Wöhler SC 602 Smart Connect

Scope of delivery: Wöhler SC 602 Smart Connect, Batteries, Hand loop, Bag
Article no. 10184

Accessories Sets



Comfort-Set Gas

Plastic case MAXI, Connection adapter, Sealing plug 16 - 32 mm (blue), Sealing plug 21 - 44 mm (blue), High-pressure plug 1 ¼" with barbed fitting MAXI (2 pieces), Single shut-off 1/8", Tightness test manifold, Single-pipe measuring cap, Disposable syringe 150 ml, Nozzle pressure measuring set, Aluminium pressure pump



Professional-Set Gas

Plastic case MAXI, Connection adapter, Sealing plug 16 - 32 mm (blue), Sealing plug 21 - 44 mm (blue), High-pressure plug 1 ¼" with barbed fitting MAXI (2 pieces), High-pressure step plug G1/2 G1 MS, High pressure step plug G3/8 G 3/4 MS, Single shut-off 1/8", Tightness test manifold, Single-pipe measuring cap, Disposable syringe 150 ml, Nozzle pressure measuring set, Aluminium pressure pump, Wöhler GS 300 gas sniffer, Wöhler TD 100 Thermal printer

Article no.

10092

10089

Accessories



Pressure Measurement Set

for Wöhler Digital Manometer
One 1.5 m measuring hose Ø 7.5 mm / Ø 3.5 mm each, plastic T-pieces 4 and 8 mm, plastic connector 4 mm, plastic reducer 4 to 8 mm



Wöhler Gas Pipe Tightness Set

Valve block with 4 connection hoses (length 1m), with fast connection each, 2 conical closing plugs, Single closure, Pressure pump



Adapter Gas Counter DN 32

with connector maxi



High Pressure Plug 1/2" and 1"

with gasket rings



High Pressure Plug 3/8" & 3/4"

with gasket rings



High Pressure Plug 1 ¼"

with plug nipple Maxi
for two-pipe gas meter 2 pack



High Pressure Lock 1/8"



Connection Adapter



Disposable Syringe 150 ml



Plastic Case M 6xx MAXI Gas



Plastic Case M 6xx MIDI Gas



Service Bag

Silicon grease, Wadding filters, O-ring, Smart Plug



Wöhler TD 100 Thermal Fast Printer

Infrared printer with 1 roll thermal paper



Thermal Paper

10 rolls for Thermal Printer Wöhler TD 100 - 12 m long/ roll,



Battery for SC 6xx and DM 602

Li-polymer battery module
with USB-C charging port

Article no.

56126

10063

21574

7213

7214

11023

21612

11184

4765

11141

11146

9243

4160

4145

8839



Wöhler Smart Connect App

Send and process all measurement data from the Wöhler Smart Connect via Bluetooth® to mobile devices using the app.

Wöhler DM 602 Digital Manometer

Burner adjustment of gas burners






Features

- Adjustment of the gas pressure on gas fireplaces
- Measurement of the fan differential pressure
- Measurement of chimney draught
- Temperature measurement
- Integrated magnets, shock-protected housing
- Robust sensor up to 3 bar as well as high resolution measuring range (1 Pa)
- Extremely responsive display of the measured value
- Illuminated display for quick reading of the measured value
- Stable measured values in any position due to high-quality pressure sensor
- Printout of test results directly on site with the Wöhler TD 100
- Selectable measuring units

Technical Data

Differential pressure	Measuring range	±3,000 mbar
	Resolution	0.01 hPa in range -210...210 mbar otherwise 0.1 mbar
	Accuracy	< 3 % from measured value in range < ±2 mbar better than ±0.06 mbar
Internal temperature measurement	Measuring range	-20...60 °C
	Resolution	0.1 °C
	Accuracy	< ±1 °C
External temperature measurement (with connected temperature sensor)	Measuring range	-20...800 °C
	Resolution	0.1 °C
	Accuracy	< ±1 °C in range -20...67 °C otherwise 1.5 % from measured value according to EN 50379-1

Accessories Sets	Article no.
 Accessory Set Nozzle Pressure Scope of delivery: Case MINI, Nozzle pressure measuring set	10094
 Accessory Set Chimney Draft Plastic case MINI, Measurement hose with probe and thread cone	10093
 Pressure Measurement Set for Wöhler Digital Manometer One 1.5 m measuring hose Ø 7.5 mm / Ø 3.5 mm each, plastic T-pieces 4 and 8 mm, plastic connector 4 mm, plastic reducer 4 to 8 mm	56126



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_183



Wöhler DM 602 Digital Manometer
Display indication in mbar and °C
Scope of delivery: Wöhler DM 602 Digital Manometer, Batteries, Hand strap, Measuring hose 1.5 m
Article no. 8837

YOU CAN TRUST US!



- ✓ Verified identity
- ✓ Encrypted data transfer
- ✓ Clear ordering process



More information on our website: wohler.co.uk

Wöhler GS 220 Gas Sniffer

Display in five steps from 40 to 920 ppm



Applications

- Leakage detection of gas lines carrying combustible gases

Features

- Calibrated for methane (CH4) and liquid petrol gas (LPG)
- Highly sensitive and quick response
- 440 mm flexible gooseneck for easy access of hard to reach spots
- Handheld unit

Technical Data

Sensitivity	Methane	40...640 ppm
	Propane	60...920 ppm
Sensor	Semiconductor	
Flexarm	Measuring range	440 mm
Warm-up time	approx. 50 sec.	
Reaction time	approx. 10 sec.	

Wöhler GS 220 Gas Sniffer

Scope of delivery: Wöhler GS 220 gas sniffer with 440 mm-gooseneck, batteries and plastic case
Article no. 6606

Wöhler GS 300 Gas Sniffer

Display in twelve steps from 0 to 1,200 ppm



Applications

- Highly sensitive and quick responsive Gas Sniffer for tightness control and leakage detection of gas lines carrying combustible gases

Features

- Acoustic signal and vibration alarm to display even the smallest leaks
- Display of gas concentration via bar graph in twelve levels from 0...1,200 ppm
- Perfect tool to control natural gas, as well as liquified gas installations
- Additional LED lighting turns on automatically in dark places, to search for leaks in hard to reach spots (flash-light function)

Technical Data

Sensitivity	Methane	0...1,200 ppm
	Propane	0...1,200 ppm
Sensor	Semiconductor	
Alarm function	visual, acoustic, vibrating	
Flexarm	440 mm	
Warm-up time	approx. 60 sec.	
Reaction time	approx. 10 sec.	



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_56



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_155



Wöhler RL 200 Refrigerant Leak Detector

For leakage control and leak detection on refrigerant systems



- Features**
- Precise and reliable detection of the smallest leaks due to high sensitivity (3 g/a)
 - Meets the requirements of the F-Gas Regulation and BS EN 14624:2012
 - Easy to use due to digital display and automatic zero value setting



Technical Data		
Tested for	R134a	
Sensitivity (R134a)	3 g/a	
Response time (R134a)	< 1 s	
Detectable refrigerants	FCKW	R11, R12, R500, R503
	HFCKW	R22, R123, R124, R502
	HFKW	R134a, R404a, R410a, R407C, R32
	others	R290, R600a, R1234YF, Forming Gas (95% N ₂ + 5% H ₂)
Sensor	Zeroing	Automatic or manual

Wöhler RL 200 Refrigerant Leak Detector
Scope of delivery: Wöhler RL 200 Refrigerant Leak Detector, Gooseneck 440 mm, Batteries, Plastic case
Article no. 11361

Wöhler RL 300 Refrigerant Leak Detector

For checking for leak detection on refrigeration systems and heat pumps



- Features**
- Precise and reliable detection of the smallest leaks thanks to high sensitivity (3 g/a)
 - Automatic zero value setting
 - Fulfils the requirements of the F-Gas Regulation and DIN EN 14624:2020
 - Digital bar graph display of the refrigerant concentration in 11 levels
 - Visual, acoustic and vibration alarm
 - The display lighting and two LED lamps switch on automatically in dark surroundings

Technical Data		
Tested for	R134a, R1234yf und R290	
Sensitivity (R134a)	3 g/a	
Response time (R134a)	2.1 s	
Detectable refrigerants	FCKW	R11, R12, R500, R503, R502
	HFCKW	R22, R123, R124
	HFKW	R134a, R404a, R410a, R407C, R32
	others	R290, R600a, R1234YF, Forming Gas (95% N ₂ + 5% H ₂)
Sensor	Zeroing	Automatic or manual

Wöhler RL 300 Refrigerant Leak Detector
Scope of delivery: Wöhler RL 300 Refrigerant Leak Detector with gooseneck 440 mm, Batteries, Plastic case
Article no. 3832

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_196



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_204



Wöhler MR 400 Refrigerant Manifold

Maintenance work on refrigeration systems and heat pumps



- Features**
- Maintenance work on refrigeration systems and heat pumps
 - Diagnosis of operating states of refrigerants in refrigerant circuits
 - Indication of high and low pressure
 - Measurement of superheating and subcooling
 - Vacuum measurements

Technical Data		
Pressure	Measuring range	-1...55 bar
	Accuracy	±0.5 % of the full scale value
	Resolution	0,03 bar
Temperatur	Measuring range	-40...150 °C
	Accuracy	±0.5 °C
	Resolution	0.1 °C
Refrigerant	R410A R134a R407C R404A R32 R290 R1234yf R514A R600A R513A	



Wöhler RS 400 Refrigerant Scale

Weight measurement to determine the contents of pressure vessels

- Features**
- Can be used with all common refrigerants
 - Easy handling due to practical accessories, for example lockable connection hoses (ball valves)
 - Everything is in view on the digital displays of the units
 - Easy storage and transport due to the plastic case and high-quality carrying bag

Technical Data		
Weight	Measurement range	0...100 kg
	Accuracy	± 0.5 % of the measured value + 10
	Resolution	5 g



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_197



Wöhler MR 400 Refrigerant Manifold

Scope of delivery: Wöhler MR 400 Fitter´s aid, 3 AA batteries 1.5 V, 2 temperature clamps, Refrigerant hoses (each with 1/4" SAE thread, closable with ball valve), Transport case

Article no. 11367



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_195



Wöhler RS 400 Refrigerant Scale

Scope of delivery:Wöhler RS 400 Refrigerant Scale with operating unit, 5 x AAA batteries 1.5 V, Bag
Article no. 11363

Wöhler DC 410^{FLOW}

Ultra-fine pressure measurement from 0.01 Pa



- Features**
- 4 Pa measurement: Assessment of sufficient combustion air supply
 - Flow velocities in air ducts
 - Ultra-fine pressure measurement from a resolution of 0.01 Pa
 - Energy assessment of the heating system (heating check 2.0 in accordance with DIN EN 15378)
 - Very precise, extremely low drift
 - USB connection for data transfer to PC / notebook
 - A brief overview of the combustion air supply is provided through the graphical display
 - Data logger

Technical Data			
Differential Pressure	Range	±100 hPa	
	Accuracy	< 3 % of the reading, if the value is < ±5 Pa, better than ±0.15 Pa	
	Resolution	0.01 Pa within the range ±110 Pa 0.1 Pa within the range ±1,000 Pa otherwise 1 Pa	
Temperature (internal sensor)	Range	-20...60 °C	
External temperature probe	Range	2 canals -20...800 °C	

Wöhler DC 410^{FLOW}

Standard Set

Scope of delivery: Wöhler DC 410^{FLOW} Pressure Differential & Flow Meter, rechargeable batteries and charger, 2 capillary hoses, Wöhler DC 4xx case

Article no. 9286

Accessories Sets		Article no.
	Comfort Set for Wöhler DC 410 FLOW Scope of delivery: Batteries, Charger, Telescopic flow probe, Clamp holder, Sealing element, Hose capillary, Air temperature sensor, Case	6468
	Accessory set professional EN-FR-NL-CZ Rechargeable batteries and charger, Wöhler TD 100 fast thermal printer, Wöhler PC software EN-FR-NL-CZ, Capillary hoses, Wöhler telescopic flow probe with probe holder and sealing element, Air temperature probe, Plastic case Maxi	6418

Accessories		Article no.
	Wöhler Telescopic Flow Probe Air velocity and temperature measurement, System measurement in rectangular ventilation ducts (Trivial method according to DIN EN 12599), Volumetric flow rate measurement in round ventilation ducts (Method of centroidal axis according to DIN EN 12599)	1012
	Pitot tube Ø 7 mm 35 cm	9487
	50 cm	9488
	100 cm	9489
	Flexible Capillary Hose 3m for Wöhler DC 410FLOW differential pressure measurement between adjoining rooms with Wöhler DC 410Flow, 1 x capillary hose 3 m, connector, silicone hose	4515
	Pipe Surface Temperature Probe with Velcro thermocouple type K for pipes up to Ø 100 mm	1126
	Surface Temperature Sensor encapsulated For plug-in flue gas probes Wöhler A 450 / A 550 / A 400 / A 500 / A 600 / DC 410 and DT 310 in accordance with DIN EN 15378 Heating check 2.0 For measuring the surface temperature on boilers, ceilings and walls, determining the U-value, etc. Measuring range up to 100 °C. During measurement, the sensor element is protected from external temperature influences by a housing sealed with a round sealing ring. When assessing the energy efficiency of heating systems (heating check), e.g. as part of a customer consultation, the temperature sensor can be used to assess the surface loss of the boiler.	4651
	Surface Temperature Probe with clamp, range up to 100°C, clamp for pipes Ø 6 - 35 mm	6679
	Surface Temperature Probe TF1 Thermocouple type K, up to max. 500°C / 392°F	6625
	Surface Temperature Probe TF2 Thermocouple type K, up to max. 500°C / 932°F	6626
	Penetration Temperature Probe TF4 for Wöhler DC 410Flow / DT 310 Thermocouple type K, up to max. 600°C / 1112°F	6629
	Data Exchange Software for DC 4xx / DP 600 / DP 700 / CFM 600 EN-FR-NL-CZ The Software can be downloaded. You will receive a separate email including the link.	1005
	Mini USB Interface Cable	2024
	Wöhler TD 100 Thermal Fast Printer Infrared printer with 1 roll thermal paper	4160
	Thermal Paper 10 rolls for Thermal Printer Wöhler TD 100 - 12 m long/ roll,	4145

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_118

24

7

Wöhler FA 410 Fan Anemometer

Volume flow measurement at air diffusers



Features

- Direct volume flow measurement at air diffusers in conjunction with the measuring funnel, e.g. in accordance with EN 12599 / 16211
- Integrated calculation of the volume flow from area and velocity during loop measurement
- Parallel measurement of air velocity and volume flow
- Measurement protocol via IR transmission to thermal printer
- Optional with swirl rectifier for measurements of swirl diffusers

Technical Data

Range	Flow velocity	0.5...30 m/s
	Volume flow (operating volume flow)	0...99,999 m³/h
	Temperature	-20...60 °C
	Relative humidity	0.1...99.9 %



Wöhler FA 4xx App
Send and process all measurement data from the Wöhler FA 4xx via Bluetooth® to mobile devices using the app.

Wöhler FA 410 Fan Anemometer
Scope of delivery: Wöhler FA 410, fan, 4 x AAA batteries, plastic carrying case
Article no. 4146

Wöhler FA 410 - Set Fan Anemometer set with funnel
Scope of delivery: Wöhler FA 410 Fan anemometer, 4 x AAA batteries, plastic case, Wöhler FA 4xx measuring funnel set with rectangular and round measuring funnel in a handy carrying bag; funnels can be clipped onto the fan anemometer, rectangular funnel: 346 x 346 mm, round funnel: Ø 210 mm
Article no. 4155

Accessories



Wöhler FA 4xx Airflow Cone Set
1 rectangular funnel 346 x 346 mm, 1 round funnel Ø 210 mm, transport bag

Article no.

4148

Telescope Set with Smartphone Holder
for Wöhler FA 4xx
Telescopic rod, Universal Smartphone Holder, Funnel Holder

6849

Telescopic Bar
for cone Wöhler FA 4xx

4684

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_103



£25*
DISCOUNT

STAY INFORMED AT ALL TIMES WITH OUR NEWSLETTER

You will receive £25 discount as a welcome gift when you subscribe to our newsletter!

**Vaild for orders of £150 or more!*



Register here
wohler.co.uk/newsletter/

FOLLOW US!



@wohler_uk



wohler_uk



Wohler UK




WohlerUK

Follow us on our socials and don't miss the latest insights and product releases.

Wöhler IR Temp 310 Infrared Thermometer

Detecting thermal bridges



Features

- Multifunctional infrared thermometer
 - Simple detection of thermal bridges
 - Assessment of mould growth potential
 - Assessment of the room climate
- Thermal bridge detection with coloured display of temperature tendency
- Display of the surface and dew point temperature with representation of the mould hazard potential
- Adjustable temperature limit values with acoustic, visual and haptic alarm
- External temperature sensor can be connected - e.g. surface temperature sensor, temperature sensor for determining the specific emission factor
- Display of relative humidity and dry bulb temperature
- Measuring range display via laser measuring circuit
- Storage of 50 data records (incl. emission factor)

Technical Data







Measurement Range	Internal Probe	-60...550 °C
	External Probe	-64...1,400 °C
	Relative Humidity	1...99 %
Accuracy	±1 °C or ±1 % of reading	
Resolution	0.1 °C	
Distance / Spot	12:1	
Response Time	1 sec.	
Internal Memory	50 memories with temperature and emissivity	
Emissivity Range	0.95 default, adjustable from 0.1 to 1	
Backlight	Permanent	

Wöhler IR Temp 310 Infrared Thermometer
Scope of delivery: Wöhler IR Temp 310 Infrared Thermometer, 2 x AAA batteries
Article no. 1388

Additional product

	Article no.
 Wöhler DT 310 Differential Thermometer Wöhler DT 310, 2 surface probes (type K), battery, plastic carrying case	6622

Accessories

     	Surface Temperature Sensor encapsulated For plug-in flue gas probes Wöhler A 450 / A 550 / A 400 / A 500 / A 600 / DC 410 and DT 310 in accordance with DIN EN 15378 Heating check 2.0 For measuring the surface temperature on boilers, ceilings and walls, determining the U-value, etc. Measuring range up to 100 °C. During measurement, the sensor element is protected from external temperature influences by a housing sealed with a round sealing ring. When assessing the energy efficiency of heating systems (heating check), e.g. as part of a customer consultation, the temperature sensor can be used to assess the surface loss of the boiler.	4651
	Clamp Temperature Sensor type K 1.5m cable	62616
	Pipe Surface Temperature Probe with Velcro thermocouple type K for pipes up to Ø 100 mm	1126
	Flue Gas Temperature Probe TF5 for Wöhler A 500 / DT 310 Thermocouple type K, up to max. 900°C / 1652°F	6635
	Penetration Temperature Probe TF4 for Wöhler DC 410 ^{Flow} / DT 310 Thermocouple type K, up to max. 600°C / 1112°F	6629
	Air Temperature Plug Wöhler A 450 / A 550	5517

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_179



Wöhler CDL 210 CO₂ Datalogger

Assessment of indoor air quality



Features

- Comfort display with adjustable limit values and acoustic and visual alarm function
- Datalogger with adjustable log rates
- Adjustable alarm function reminds to supply fresh air, thus preventing the spread of viruses (e.g. the corona virus) in closed rooms
- Continuous data transmission for online measurement and monitoring

Technical Data

CO ₂ -measurement	Measuring range	0...9,999 ppm
	Resolution	1 ppm
	Accuracy	±50 ppm ±5 % from measured value (0...2,000 ppm)
Temperature	Measuring range	-10...60 °C
	Resolution	0.1 °C
	Accuracy	±0.6 °C (±0.9 °F)
Humidity	Measuring range	5...95 % r.h.
	Resolution	0.1 % r.h.
	Accuracy	at 10...90 % 25 °C: ±3 % r.h. otherwise: ±5 % r.h.
Power supply	AC power supply 5V	

Wöhler IQ 300 CO₂ Meter

Indoor air quality monitoring

Features

- The Wöhler IQ 300 CO2 meter is ideal for monitoring air quality in classrooms, waiting rooms, seminar rooms, etc.
- Via a bright traffic light LED and a clear audible tone, the Wöhler IQ 300 warns when ventilation is required
- Ideal for monitoring indoor air quality (good, normal, poor)
- Bright traffic light LED bar
- Alert tone
- Large display of the CO₂ level
- Adjustable to individual preferences
- Trend display on the development of indoor air quality

Technical Data

Carbon dioxide	Range	0...9,999 ppm
	Resolution	1 ppm
	Accuracy	±50 ppm ±5 % of measured value at 0...2.000 ppm ±10 % of measured value at > 2,000 ppm
°C-Measure-ment	Range	-0...50 °C
	Resolution	0.1 °C
	Accuracy	±0.6 °C (0.9 °F)
Rel. air humidity	Range	0.1...99.9 %
	Resolution	0.1 % r.h.
	Accuracy	±5 % at 10...90 % r.h. and 25 °C, other-wise 7 %



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_113



Wöhler CDL 210 CO2-Data logger

for assessing indoor air quality and the ventilation situation, as well as for analysing problems

Scope of delivery: Wöhler CDL 210 CO₂-Data Logger, power supply unit, USB data cable and PC software

Article no. 6648

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_193



Wöhler IQ 300 CO₂ Meter

to assess the indoor air quality and ventilation situation

Scope of delivery: Wöhler IQ 300, power supply

Article no. 4750

Wöhler CM 220 Carbon Monoxide Meter

Assessment of air quality



Applications

- Measurement of CO concentration in the ambient air
- Test CO leakage from furnaces, water heaters, stoves
- MWC-Value-Measurement (Maximum Workplace Concentration)

Features

- Quick response for testing safe entry conditions
- Easy operation-one button, manual zero
- Visual and acoustic indicators
- Backlight
- Precise electrochemical sensor
- Calculation of the MWC-value (Maximum Workplace Concentration)

Technical Data

Range	0...999 ppm
Accuracy	±20 % at 0...99 ppm ±15 % at 100...500 ppm
Resolution	1 ppm
Response time	up to 60 sec.
Humidity range	5...99 % r.h. (non condensing)

Wöhler CM 220 Carbon Monoxide Meter

Scope of delivery: Wöhler CM 220 Carbon Monoxide Meter, Batteries, Hand strap, Carrying pouch

Article no. 4486

Wöhler KM 410 IAQ Instrument

Assessment of indoor air quality

Applications

The Wöhler KM 410 IAQ Instrument is the perfect instrument for verifying HVAC system performance and air ventilation control, it measures:

- CO₂-content
- Air temperature
- Air humidity
- CO-content
- Dew point
- Wet bulb temperature

Features

- Large LC display with blue backlight to use in dark area
- Acoustical and visual alarm function
- Max/Min-values
- Hold function freezes current readings
- Mini USB output to PC for analysis
- Datalogger

Technical Data

CO ₂ measurement (NDIR-Sensor)	Measuring range	0...5,000 ppm (5,001...9,999 ppm outside the spec. range)
	Resolution	1 ppm
	Accuracy	±30 ppm ±5 % (0...5,000 ppm)
CO measurement	Measuring range	0...1,000 ppm
	Resolution	1 ppm
	Accuracy	±10 ppm for less than 100 ppm ±10 % between 101...500 ppm ±20 % over 501 ppm
Temperature	Measuring range	-20...60 °C (-5...140 °F)
	Resolution	0.1 °C (0.1 °F)
	Accuracy	±0.5 °C (±0.9 °F)
Relative humidity	Measuring range	0.1...99.9 % r.h.
	Resolution	0.1 % r.h.
	Accuracy	±3 % at 10...90 % r.h. and 25 °C, ±5 % r.h. under other values and 25 °C
Service life with continuous operation		24 hours

Wöhler KM 410 IAQ Instrument

incl. Calibration Kit

Scope of delivery: Wöhler KM 410 instrument, 4 x AA-Batteries, USB-Data Cable, PC-Software, Plastic case, Calibration kit

Article no. 10131



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_50



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_125



Wöhler VIS 500 Visual Inspection System

Visual duct, flue gas and ventilation system inspection



Features

- Damage analysis, non-destructive inspection and documentation of:
 - 87° bends
 - Sewer pipes from Ø 40 mm
 - House connections up to Ø 200 mm
 - Air pipes and ducts
 - Intermediate ceilings, cavities, shafts
 - Industrial machines / plants
- The universal camera for your applications: Interchangeable camera head, sound and voice recording via headset and different rod lengths.
- Waterproof rotatable and pan and tilt camera head Ø 40 mm for an all-round view
- Easy operating and reporting with the Wöhler video inspection app
- Bright illumination with camera LEDs and optional additional lighting
- Intuitive handling with uniform operating concept of the Wöhler VIS series

Technical Data
















Monitor	TFT display	7" / 16:9 Format
	Resolution	1,024 x 600 px
	Connection cable	2 m
	Power supply	USB-C 5 V / 3 A 3.7 V / 11.4 Ah Lithium-Ionen Akku
	Operating time	6 h
Camera rod	Length	20 / 30 m electr. meter counting

Wöhler VIS 500 Inspection Camera INT

Camera head Ø 40 mm, camera rod 30 m

Scope of delivery: Wöhler VIS 500 monitor unit with 7" TFT widescreen colour monitor incl. 2 m connection cable (monitor removable) Glare protection, Lithium-ion battery 6 h operation time, Data storage: Internal memory 4 GB expandable with USB stick, Wöhler pan and tilt camera head Ø 40 (detachable), Camera rod Ø 6.5 mm / 30 m long (removable for cleaning), USB mains charger with USB-C cable, Double sided suitcase, Replacement plastic domes (3 pieces)

Article no. 11508

Accessories		Article no.
	Wöhler L 200 Locator for camera heads Ø 26 / 40 mm for Wöhler VIS 350 / 500 / 700 Scope of delivery: Wöhler L 200 Locator, Telescopic rod, Headphones, USB power supply unit with micro USB cable, Lithographic chalk (12 pieces, yellow), Plastic case	7430
	Wöhler Miniature Camera Head Ø 26 mm Colour, detachable, with pouch for Wöhler VIS 350 / 500 Camera head with flexible connection (PAL) for GRP camera rod and leather protective bag.	420
	Wöhler Camera Head Ø40 mm detachable, pan and tilt for Wöhler VIS 350 / 500 flexible connection to camera rod, with leather protection bag	870
	Guidance Sleeve for camera head Ø 26 mm increases arc mobility and protects the camera head	3827
	Guidance Sleeve with protection cage for camera head Ø 26 mm increases arc mobility, protects the camera head and also the lens	3847
	Wöhler Light Ring 26/40, detachable for camera heads Ø 26 mm / Ø 40 mm Only for detachable camera heads - the additional lighting with 18 white LEDs is mounted between the camera head and the camera pole. Power is supplied via the video inspection system. Ø- Outside 53 mm	11398
	Protection Sleeve for Wöhler Camera Head Ø 40 mm Easy installation and secure hold thanks to clamping lever, particularly good visibility thanks to a round recess in the dome area	2641
	VIS Centering Brush for camera heads and rods Ø 20 cm, with 6 strip brushes as spacers can be fixed directly behind the camera head	3850
	VIS Centering Brush for camera rods Wöhler rod element Ø 20 cm with 6 strip brushes, threaded on one side	3854
	Camera Roller Guide suitable for camera heads and rods	3681
	Wöhler VIS Camera Trolley Set Camerahead-holder, Storage bag Wöhler, Stabilization sleeve for light ring 26/40 (can only be used in combination with supplementary light)	4753
	Replacement Plastic Domes for Wöhler Camera Head Ø 40 mm 10 pieces	3675
	Glass Dome for Wöhler Camera Head Ø 40 mm	13674
	Wöhler VIS Cleaning Set with plastic case 1 liter disinfection spray, 50 cleaning tissues, 100 disposable gloves size XL (powder free), 200 ml lubricant, plastic case For approx. 50 applications	4725
	Anti-reflective Film for monitor Wöhler VIS 500 / 700 with mounting accessories Display protection function 150 x 94 mm	7616



Wöhler Video Inspection App

The monitor image can be sent to mobile devices via WLAN and processed further using an app.

Wöhler VIS 700 HD Visual Inspection System

Visual inspection of sewers / air ducts / flue systems / industrial machinery



Features

- High Definition picture
- Focus control via joystick
- Adjustable sonde frequency
- Voice recording / photo function
- Touch screen keyboard for written commentary
- App-supported operation and report creation
















Technical Data

Monitor	TFT display	7" / 16:9 Format
	Resolution	1,280 x 800 px
	Connection cable	2 m
	Power supply	USB-C 5 V / 3 A 3.7 V / 11.4 Ah
	Operating time	4 h
Push rod	Length	20 / 30 m digital metre counting

Wöhler VIS 700 HD Inspection Camera with motor focus (manual)

Scope of delivery: Wöhler VIS 700 monitor unit with 7" HD TFT widescreen colour monitor incl. 1.5 m connection cable, Glare shield, Lithium-ion battery, Wöhler HD pan/tilt camera head Ø 40, detachable, Camera rod 8.6 x 5.6 mm - 30 m long (removable for cleaning), 3 spare plastic domes, 1 anti-slip mat, USB mains charger UK with USB-C cable, Double-shell case

Article no. 8744

Accessories	Article no.
 Wöhler L 200 Locator for camera heads Ø 26 / 40 mm for Wöhler VIS 350 / 500 / 700 Scope of delivery: Wöhler L 200 Locator, Telescopic rod, Headphones, USB power supply unit with micro USB cable, Lithographic chalk (12 pieces, yellow), Plastic case	7430
 Wöhler Light Ring 26/40, detachable for VIS 700 HD Cameras For detachable camera heads only. The additional lighting with 18 white LEDs is installed between the camera head and the camera rod. Power is supplied via the video inspection system.	8818
 Wöhler HD-Miniature Camera Head Ø 26 mm for Wöhler VIS 700 Detachable, digital camera head for colour image with leather protective case	7613
 Wöhler HD-Camera Head Ø 40 mm detachable with leather protection bag (for VIS 700)	8859
 Guidance Sleeve for camera head Ø 26 mm increases arc mobility and protects the camera head	3827
 Guidance Sleeve with protection cage for camera head Ø 26 mm increases arc mobility, protects the camera head and also the lens	3847
 Protection Sleeve for Wöhler Camera Head Ø 40 mm Easy installation and secure hold thanks to clamping lever, particularly good visibility thanks to a round recess in the dome area	2641
 VIS Centering Brush for camera heads and rods Ø 20 cm, with 6 strip brushes as spacers can be fixed directly behind the camera head	3850
 VIS Centering Brush for camera rods Wöhler rod element Ø 20 cm with 6 strip brushes, threaded on one side	3854
 Camera Roller Guide suitable for camera heads and rods	3681
 Wöhler VIS Camera Trolley Set Wöhler VIS Camera Trolley, Camerahead-holder, Storage bag Wöhler, Stabilization sleeve for light ring 26/40 (can only be used in combination with supplementary light)	4753
 Replacement Plastic Domes for Wöhler Camera Head Ø 40 mm 10 pieces	3675
 Glass Dome for Wöhler Camera Head Ø 40 mm	13674
 Wöhler VIS Cleaning Set with plastic case 1 liter disinfection spray, 50 cleaning tissues, 100 disposable gloves size XL (powder free), 200 ml lubricant, plastic case For approx. 50 applications	4725
 Anti-reflective Film for monitor Wöhler VIS 500 / 700 with mounting accessories Display protection function 150 x 94 mm	7616



Wöhler Video Inspection App

The monitor image can be sent to mobile devices via WLAN and processed further using an app.



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_16510



Wöhler VE 220 HD Video Endoscope

HD Inspection of inaccessible cavities



- Features**
- HD inspection of:
 - Inaccessible cavities through smallest openings from Ø 6 mm (e.g. tile cross)
 - Pre-wall installations, sinks, drain ducts
 - Fireplaces, combustion chambers, connectors
 - Inspection openings and fire dampers
 - Transmission of image and video data via WiFi to smartphone, laptop, tablet, PC
 - Can be used simultaneously on several devices
 - Direct forwarding of pictures and videos via "Share function" of the smartphone/tablet
 - Image and video recording
 - Switchable hand lamp
 - Compatible with Android/iOS
 - Probe length up to 10 m
 - Various probes available



Technical Data		
Signal transmission	Wireless LAN Network Standard	IEEE 802.11 b/g/n
	Data transmission rate wireless card with 802.11 a/b/g/n	up to 150 Mbit/s
HD Probe camerahead	Protection	waterproof IP 67
File formats	Image format	JPG
	Video format	AVI
Power supply	2.600 mAh Lithium-ion rechargeable battery	

Wöhler VE 400 HD Video Endoscope

HD inspection of inaccessible spaces



- Features**
- HD inspection of:
 - Inaccessible spaces through the smallest openings from Ø 4 mm (e.g. tile spacers)
 - Pre-wall installations, sinks, drain ducts
 - Fireplaces, combustion chambers, connectors
 - Inspection openings and fire dampers
 - Large 5" HD colour monitor
 - HD Video Endoscope waterproof probes
 - Image rotation
 - Image and video recording on Micro-SD Card
 - Additional lamp on the unit with 4 LEDs to illuminate the inspection area
 - Ø 3.9 mm probe for smallest inspection openings
 - Switchable 0°/ 90° straight line / side view probe Ø 5.5 mm
 - Various probes available

Technical Data		
Monitor	Display	5"
	Resolution	1,280 x 720 px
	Interfaces	Micro-USB-Data / charging connection Micro-SD Card slot
HD Probe camera head	Protection class	waterproof IP 67
File formats	Image format	JPG
	Video format	MP4
Power supply	Lithium-ion rechargeable battery	
Operating time	4 hours	



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_136



Wöhler VE 220 HD Video Endoscope
HD Probe 1 m, Ø 7.6 mm
Scope of supply: Wöhler VE 220 HD Video Endoscope with 1.0 m probe Ø 7.6 mm, side tip mirror, magnet, hook tool, plastic case
(The VE 220 is not compatible with a Windows Phone)
Article no. 12132

Wöhler VE 400 HD Video Endoscope
HD Probe 1 m, Ø 5.5 mm, view 0° / 90°
Scope of delivery: Wöhler VE 400 HD Video Endoscope, HD-Video-Endoscope-probe 0° / 90° / Ø 5.5 mm / 1 m, Lithium-ion battery, Micro SD card 16 GB, Micro USB charger, Extension cable 1.5 m, Case
Article no. 6920

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_169



Wöhler VE 500 HD Video Endoscope

Inspection of inaccessible spaces / with integrated monitor



Features

- HD inspection of:
 - Inaccessible spaces through the smallest openings from Ø 4 mm
 - Pre-wall installations, spouts, drainage pipes, fireplaces, combustion chambers, connecting pieces
 - Inspection openings and fire damper
- Large colour monitor
- Image rotation
- Split screen mode
- Stand for positioning the monitor
- Can be used on several devices simultaneously
- Additional LED lamp on the endoscope to illuminate the inspection area
- Various probes available









Technical Data

Monitor	Size	7"
	Resolution	1,280 x 720 px
	Interfaces	Micro-USB data / charging port Micro SD card slot
Video endoscope HD Probe camera head	Protection class	IP 67
Recording formats	Image file	JPG
	Video file	AVI
Power supply	Lithium-ion rechargeable battery	
Operating time	5 – 6 h	

Wöhler VE 500 HD-Video-Endoscope
incl. probe Ø 5.5 mm / 1 m / 90°

Scope of delivery: Wöhler VE 500 HD Video Endoscope with WiFi function and USB C, HD Video Endoscope combination probe Ø 5.5 mm / 1 m / 90°, Lithium-ion battery, Micro SD card 32 GB, USB charger, Connection cable 1.5 m, Carrying case

Article no. 11390

Accessories	Article no.
	HD-Video-Endoscope-Probe Ø 3.9 mm / 1 m Not compatible with Wöhler VE 300 video endoscopes. 6929
	HD-Video-Endoscope-Probe Ø 25 mm / 3 m For use in waste water / flue gas pipes from Ø 40 mm. Not compatible with Wöhler VE 300 video endoscopes. 6911
	HD-Video-Endoscope-Probe 0° / 90° Ø 5.5 mm / 1 m / 90° Two cameras with viewing angles of 90° (focus length 20-50mm) and 0° (focus length 30-80mm) as well as a preset focus range (78°) per camera lens. 11415
	HD-Video-Endoscope-Probe (3 Cameras) Ø 25 mm / 5 m / 180 ° with roller guide Not compatible with Wöhler VE 300 Video Endoscopes. 11419
	HD-Video-Endoscope-Probe (3 Cameras) Ø 25 mm / 10 m / 180 ° for Wöhler VE 500 11418
	HD-Video-Endoscope-Probe (3 Cameras) Ø 7.9 mm / 10 m / 180° for Wöhler VE 500 11417
	HD-Video-Endoscope-Probe, swivelling Ø 6.2 mm / 1.5 m / 180° incl. bag and 1 m connection cable. with 8 LEDs, focus distance 20 - 100mm, FoV 100°. Compatible with current Wöhler VE series. 11321
	Video-Endoscope-Connection-Cable 1.5 m For extending the connection between the Wöhler VE video endoscope and the video endoscope probes. Not compatible with Wöhler VE 300 video endoscopes. 6931
	Magnetic Holder for securely attaching the HD video endoscope to magnetic surfaces. Included magnets can be used for Wöhler VE 500 HD-video-endoscope. 6986
	Protection Bag for Wöhler VE series and probes 6914
	HD-Video-Endoscope-Probe (2 Cameras) Ø 8.5 mm / 3 m / 90° for Wöhler VE 500 Two cameras with viewing angles of 90° (focus length 20-50mm) and 0° (focus length 30-80mm) as well as a preset focus range (78°) per camera lens. 11416
	Large Protective Bag Video-Endoscopes for Wöhler VE series and probes 10185

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_199





HD-Video-Endoscope-Probe
Ø 3.9 mm / 1 m
Article no. 6929



HD-Video-Endoscope-Probe
Ø 5.5 mm / 1.2 m
Article no. 7787



HD-Video-Endoscope-Probe
Ø 25 mm / 3 m
Article no. 6911



HD-Video-Endoscope-Probe
(2 Cameras)
Ø 5.5 mm / 1 m / 0° / 90°
Article no. 11415



HD-Video-Endoscope-Probe
(2 Cameras)
Ø 8.5 mm / 3 m / 0° / 90°
Article no. 11416



HD-Video-Endoscope-Probe
(3 Cameras)
Ø 7.9 mm / 10 m / 0° / 2 x 90°
Article no. 11417



HD-Video-Endoscope-Probe
(3 Cameras)
Ø 25 mm / 5 m / 0° / 2 x 90°
with roller guide
Article no. 11419



HD-Video-Endoscope-Probe
(3 Cameras)
Ø 25 mm / 10 m / 0° / 2 x 90°
with roller guide
Article no. 11418



HD-Video Endoscope-Probe
(swivelling)
Ø 6.2 mm / 1.5 m / 180°
Article no. 11321



Large protective bag
for Wöhler VE series
and probes
Article no. 10185




Protection bag
for Wöhler VE series
and probes
Article no. 6914

WÖHLER

SOME THINGS YOU'VE NEVER SEEN. UNTIL NOW.



Nobody knows what you will find behind some walls of this world. But with Wöhler, you can be sure to see it clearly!



[wohler.co.uk/
endoscopes](http://wohler.co.uk/endoscopes)

Made in Germany

Wöhler RM 200 Drain Cleaning Machine

Modular entry system for cleaning inner pipes



Features

- Cleaning of:
 - Waste water pipes Ø 40...100 mm
 - Blockages of various degrees
 - Grease deposits on pipe walls
 - Sludgy and silted deposits
- Particularly good for getting started with pipe cleaning
- Spiral length can be determined by yourself using a handy spanner for the spiral connections
- Protective hose for clean cleaning and protection of domestic equipment
- Adapter with integrated spiral for safe use
- Various spiral sizes for cleaning pipes indoors
- Modular system: Heads and spirals are compatible with each other
- Easy change of direction of rotation thanks to switch within easy reach
- Flexible: Quick changeover of the heads

Technical Data







Input Power	400 W
Rated Voltage	220 V / 50 Hz
Weight	12.2 kg
Spiral Sizes	Ø 8 mm / 5 m
	Ø 16 mm / 2.3 m
Max. Cable Length	40 m
Tube Diameter	Ø 40...100 mm

Wöhler RM 200 Drain Cleaning Machine

Scope of delivery: Wöhler RM Drain Cleaning Machine, 1 cable drum for drain cleaning cable, 8 drain cleaning cables Ø 16 mm Length: 2.3 m, 1 guide hose, 1 carrying case for drain cleaning accessories, 1 adapter with bulb auger and cable 8 mm, 1 Straight auger Ø 16 mm, 1 Blub auger Ø 16 mm, 1 Spade cutter Ø 16 mm, 1 C-Cutter Ø 16 mm, 1 coupling key 4 mm, 1 pair of drain cleaning protection gloves

Article no. 11220

Accessories

	Article no.
 Wöhler PU 100 Pipe Cleaning Pump Wöhler PU 100 Pipe Cleaning Pump, 3 adapters for toilet / sink / shower, Carrying Case	11240
 Spiral 16 mm x 2.3 m for Wöhler RM 200/ RM 300	11212
 Coupling Key 4 mm for Wöhler RM 200/ RM 300	11207
 Straight Auger 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11215
 Bulb Auger 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11217
 Spade Cutter 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11219
 C-Cutter 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11222
 Accessories Case for Drain Cleaning Attachments	11200

INSPECT BEFORE YOU CLEAN!

The Wöhler Drain Cleaning Machine is ideal for removing clogs in household drains. However, to identify key issues within the pipes and ensure that all problems are resolved, Wöhler Video Inspection Systems are essential.

These systems enable you to examine, pinpoint, and verify conditions to provide your customers with top-notch results.



Find out more online at wohler.co.uk/inspection-camera



Wöhler RM 300 Drain Cleaning Machine

Powerful system for cleaning inner and outer pipes






Features
















- Cleaning of:
 - Waste water pipes Ø 40...110 mm / Ø 50...150 mm
 - Blockages of various degrees
 - Grease deposits on pipe walls
 - Sludgy and silted deposits
- With an output of 570 W, pipe blockages can be removed indoors and outdoors
- Spiral length can be determined by yourself using the handy spanner for the spiral connections
- Protective hose for clean cleaning and protection of domestic equipment
- Adapter with integrated spiral for safe use
- Various spiral sizes for cleaning all pipes indoors
- Modular system: Heads and spirals are compatible with each other
- Easy change of direction of rotation thanks to switch within easy reach
- Flexible: Quick changeover of the heads

Technical Data

Input Power	570 W
Rated Voltage / Rated Frequency	220 V / 50 Hz
Weight	18.2 kg
Spirale Sizes	Ø 8 mm / 5 m
	Ø 16 mm / 2.3 m
	Ø 22 mm / 4.6 m
Max. Cable Length	65 m
Tube Diameter	Ø 40...100 mm
	Ø 50...150 mm

Wöhler RM 300 Drain Cleaning Machine
Scope of delivery: Wöhler RM 300 Drain Cleaning Machine
Article no. 11208

Accessories Sets	Article no.
 Accessory Set 16 mm Straight Auger 16 mm, Bulb Auger 16 mm, Spade Cutter 16 mm, Spiral 16 mm x 2.3 m (8 pieces) with spiral reel, Coupling Wrench 4 mm, Protective Hose, Protective Gloves, Accessory Box	11257
 Accessory Set 22 mm Straight Auger 22 mm, Bulb Auger 22 mm, Spade Cutter 22 mm, C-Cutter 22 mm, Spiral 22 mm x 4.6 m (4 pieces) with spiral reel, Coupling Wrench 5 mm, Protective Hose, Protective Gloves, Accessory Box	11258
 Accessory Set 16 / 22 mm Straight Auger 16 mm, Straight Auger 22 mm, Bulb Auger 16 mm, Bulb Auger 22 mm, Spade Cutter 16 mm, Spade Cutter 22 mm, C-Cutter 16 mm, C-Cutter 22 mm, Spiral 16 mm / 2.3 m (8 pieces), Spiral 22 mm / 4.6 m (4 pieces), Spiral Reel, Spiral Adapter 8 mm / 5 m, Coupling Wrench 4 mm, Coupling Wrench 5 mm, Protective Hose, Protective Goves, Accessory Box	11190

Accessories	Article no.
 Wöhler PU 100 Pipe Cleaning Pump incl. adapter Wöhler PU 100 Pipe Cleaning Pump, 3 adapters for toilet / sink / shower, Carrying Case	11240
 Spiral 16 mm x 2.3 m for Wöhler RM 200/ RM 300	11212
 Spiral 22 mm x 4.6m for Wöhler RM 300	11213
 Protection Hose for Wöhler RM 300	11211
 Coupling Key 4 mm for Wöhler RM 200/ RM 300	11207
 Coupling Key 5 mm for Wöhler RM 300/ RM 400	11209
 Straight Auger 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11215
 Straight Auger 22 mm for Wöhler RM 300/ RM 400 Waste water pipes Ø 70...150 mm	11216
 Bulb Auger 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11217
 Bulb Auger 22 mm for Wöhler RM 300/ RM 400 Waste water pipes Ø 70...150 mm	11218
 Spade Cutter 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11219
 Spade Cutter 22 mm for Wöhler RM 300/ RM 400 Waste water pipes Ø 70...150 mm	11221
 Accessories Case for Drain Cleaning Attachments	11200
 C-Cutter 16 mm for Wöhler RM 200/ RM 300 Waste water pipes Ø 40...100 mm	11222
 C-Cutter 22 mm for Wöhler RM 300/ RM 400 Waste water pipes Ø 70...150 mm	11223

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_175



Wöhler RM 400 Drain Cleaning Machine

Convenient system for cleaning inner and outer pipes



Features

- Cleaning of:
 - Waste water pipes Ø 50...150 mm
 - Blockages of various degrees
 - Grease deposits on pipe walls
 - Sludgy and silted deposits
- The spiral integrated into the drum enables clean and comfortable working
- Automatic feed for easier use of the device
- Easy transport thanks to wheels on the device
- Solving stubborn blockages through high performance
- Various spiral sizes for cleaning all pipes indoors
- Modular system: Heads and spirals are compatible with each other!
- Easy change of direction of rotation thanks to switch within easy reach
- Flexible: Quick changeover of the heads

Technical Data

Input Power	390 W
Rated Voltage / Rated Frequency	220 V / 50 Hz
Weight	41.78 kg
Spirale Sizes	Ø 16...22 mm / 23 m
Max. Cable Length	23 m
Tube Diameter	Ø 50...110 mm

Wöhler RM 400 Drain Cleaning Machine

Scope of delivery: Wöhler RM 400 Drain Cleaning Machine, Straight Auger 22 mm, Bulb Auger 22 mm, Spade Cutter 22 mm, C-Cutter 22 mm

Article no. 11230

Accessories



Wöhler PU 100 Pipe Cleaning Pump
incl. adapter
Wöhler PU 100 Pipe Cleaning Pump, 3 adapters for toilet / sink / shower, Carrying Case

Article no.

11240



Coupling Key 5 mm
for Wöhler RM 300/ RM 400

11209



Straight Auger 22 mm
for Wöhler RM 300/ RM 400
Waste water pipes Ø 70...150 mm

11216



Bulb Auger 22 mm
for Wöhler RM 300/ RM 400
Waste water pipes Ø 70...150 mm

11218



Spade Cutter 22 mm
for Wöhler RM 300/ RM 400
Waste water pipes Ø 70...150 mm

11221



C-Cutter 22 mm
for Wöhler RM 300/ RM 400
Waste water pipes Ø 70...150 mm

11223



Accessories Case
for Drain Cleaning Attachments

11200

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_173



WÖHLER
ACADEMY

CLEANING

Application knowledge around the topic of cleaning technology

Here you will find helpful knowledge about applications around cleaning technology.

- ▶ Cleaning of ventilation systems / air ducts with brushes
- ▶ Cleaning of a ventilation system / air duct with compressed air
- ▶ Sewer Pipe Cleaning With A Drain Cleaning Machine
- ▶ Chimney cleaning

Scan
now!



wohler.co.uk/
Cleaning



Wöhler Snap & Sweep® System

Effective sweeping with rotating cleaning tools












Features

- One system - many applications: Freestanding stainless steel flues, large-volume flues, large air ducts, basic cleaning before renovation, removal of jackdaw nests
- Stable plastic plug-in connection - cleaning without damage even in stainless steel flues, air ducts
- Snap lock for quick and easy handling, even with gloves
- Gentle sweeping with bump brushes and thread twists, powerful sweeping with chains
- One-man operation: You can easily do it alone
- Rotary drive with commercially available cordless screwdriver
- The perfect rod length for every work step
- Comfortable and clean transport in the carrying bag

Technical Data

Material	Plastic	
Length	1 m	
Operating temperature	Soft	-5...85 °C
	Regular	-20...85 °C
	Strong	-20...85 °C
Connections	1 plug-in connection and 1 receptacle each	
Colour	Soft	Blue
	Regular	Black
	Strong	Red
Flexural rigidity	Soft	ca. 47 kN cm²
	Regular	ca. 118 kN cm²
	Strong	ca. 189 kN cm²

Accessories		Article no.
	Cleaning rod 1m Wöhler Snap & Sweep® Soft	1287
	Rotary Head, Nylon wires Universal rotary head Wöhler Snap&Sweep Nylon wires, 6 pcs., 3 mm, length: each 50 cm	8784
	Universal Rotary Head with snap in connectors	8786
	Push Head Adapter Threaded/Perlon Brush with M10 thread for holding M10 threaded & perlon brush	8978
	Nylon Wire 6 pcs., 3 mm, length: each 30 cm	24468
	6 pcs., 3 mm, length: each 50 cm	24469
	Drill Adaptor for cordless screwdriver	2942
	Carrying Bag for Rods Wöhler Snap & Sweep® for up to 15 rods	61062
	Protection Bag for Sweeping Tools Wöhler Snap & Sweep®	55703
	Repair Set Wöhler Snap & Sweep® incl. connector end piece, connector start piece, pan head screws Ø 2.5 x 10 mm (6 pcs.)	11172

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_15220



Wöhler Snap & Sweep® Soft Professional Set "Ventilation"

Scope of delivery: 10 cleaning rods with snap in quick connectors, carrying bag rods, perlon brush Ø 25 cm / 0,8 mm, universal rotary head with nylon wires 3 mm / 6 x 50 cm, drill adaptor, protection bag brushes, Push rod 0.5 m with handle piece

Article no. 8365

Wöhler Rotary Viper Duct M5

Flexible with wiper and brush head



Features

- Cleaning of:
 - Round air ducts from Ø 63 mm
 - Flat oval ducts from 50 x 100 mm
 - Controlled domestic ventilation
 - Ducts contaminated with grinding dust
 - Dryer vents
- Very flexible shaft and head:
 - Small perlon head Ø 14 cm
 - Wiping head to remove dust
- Can be operated with cordless screwdriver

Technical Data

Length	5 / 15 m
Max. torque	Clockwise rotation 3 Nm Counterclockwise rotation 1.5 Nm
Operating temperature	0...80 °C
Connection cleaning attachment	M5 thread

Wöhler Rotary Viper Vent 5 m compact with wipe and brush head

Scope of delivery: Wöhler Rotary Viper Vent 5 m, Brush head, perlon Ø 140 mm, Wipe head with two wiping cloths each Ø 150 mm

Article no. 7192

Wöhler Rotary Viper - M5 head 15m

Scope of delivery: Wöhler Rotary Viper Duct - 15 m, Brush head perlon Ø 140 mm, Wipe head with two wiping cloths Ø 150 mm

Article no. 4172

Brush head Perlon Ø 14 cm Wöhler Rotary Viper - M5 head

Article no. 4169

Wöhler Rotary Viper Duct M10

Cleaning of ventilation systems

Features

- Effective cleaning of dryer vents, duct and piping
- CW/CCW rotation
- Due to a small end piece also applicable for smaller bends
- Very light weight 1.3 kg
- Extremely flexible shaft
- Can be operated with cordless screwdriver

Technical Data

Length	1.5 / 3 / 5 / 10 / 15 m
Max. torque	Clockwise rotation 3 Nm Counterclockwise rotation 1.5 Nm
Operating temperature	0...80 °C
Connection cleaning attachment	M10 thread

Wöhler Rotary Viper M10 Ventilation - 1.5 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 1.5 m, brush head perlon Ø 18 cm
Article no. 4882

Wöhler Rotary Viper M10 Ventilation - 3 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 3 m, brush head perlon Ø 18 cm
Article no. 4867

Wöhler Rotary Viper M10 5 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 5 m, brush head perlon Ø 18 cm
Article no. 4832

Wöhler Rotary Viper M10 Ventilation Set - 5 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 5 m, brush head perlon Ø 18 cm, brush head perlon Ø 25 cm, threaded brush perlon Ø 30 cm
Article no. 7511

Wöhler Rotary Viper M10 Ventilation - 10 m


Scope of delivery: Wöhler Rotary Viper Ventilation - 10 m, brush head perlon Ø 18 cm
Article no. 4866

Wöhler Rotary Viper M10 Ventilation - 15 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 15 m, Brush head perlon Ø 18 cm
Article no. 4880

Wöhler Rotary Viper M10 Ventilation - 3 m

Scope of delivery: Wöhler Rotary Viper Ventilation - 3 m, brush head perlon Ø 18 cm
Article no. 4867



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_13830



Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_13820



Wöhler Viper S

Cleaning of openings from Ø 40 mm



- Features**
- Cleaning of:
 - Exhaust pipes Ø 40 – 150 mm
 - Connectors
 - Small air ducts
 - GRP rod with abrasion-resistant PA sheath
 - Provides splash protection when inserting the wet GRP rod
 - Ergonomically shaped handle
 - 2 coupling holders – for right and left-handers
 - Fits in the Wöhler tool carrier and backpack measuring case
 - For holding HT mini hole stars and HT pipe brushes

Technical Data	
Basket diameter	28 cm
Width	3.3 cm
Weight	0.84 kg including 15 m GRP rod



Wöhler Viper M PLUS

With digital metre counting – internal M10 thread

- Features**
- Cleaning of:
 - Exhaust systems up to approx. Ø 250 mm
 - Connecting pieces up to approx. Ø 250 mm
 - Air ducts
 - Digital metre counting
 - Quick-change push head for convenient changing of line stars
 - GRP rod with abrasion-resistant PA sheath and protective hose
 - Precisely adjustable freewheel brake and transport lock
 - Transport option with star holder with protective plate for two additional line stars
 - Coupling holder for sweeping and transporting
 - For holding line stars and threaded brushes

Technical Data	
Basket diameter	42 cm
Weight	Approximately 2 kg incl. 15 / 20 m GRP rod
Freewheel brake	Precisely adjustable
GRP rod	Ø 7 mm
Stainless steel end piece	M10





Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_16



Wöhler Viper S
15 m
Scope of delivery: GRP Rod 4.5 mm, 15 m stainless steel end piece M5, guidance adapter (without stars)
Article no. 2028

Wöhler Viper M PLUS
15 m - with digital metre counter
Scope of delivery: GRP Rod 7 mm Ø, 15 m with stainless steel end pieces M10, quick change star holder to hold stars and GRP push head for mounting stars (without stars)
Article no. 3770

Wöhler Viper M PLUS
20 m - with digital metre counter
Scope of delivery: GRP Rod 7 mm Ø, 20 m with stainless steel end pieces M10, quick change star holder to hold stars and GRP push head for mounting stars (without stars)
Article no. 3790

















Wöhler online shop













Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_17



Accessories		Article no.
	Star, HT 28 mm / 1.1" inner hole diameter temperature resistant up to 250°C Ø 15 cm / 6"	12815
	Ø 18 cm / 7.1"	12818
	Ø 20 cm / 8"	12820
	Ø 25 cm / 10"	12825
	Ø 30 cm / 12"	12830
	Star Perlon 28 mm / 1.1" inner hole diameter Ø 15 cm / 6"	13715
	Ø 18 cm / 7.1"	13718
	Ø 20 cm / 8"	13720
	Ø 25 cm / 10"	13725
	Ø 30 cm / 12"	13730
	Ø 40 cm / 15.7"	24
	Star HT 16 mm / 0.6" inner hole diameter temperature resistant up to 250°C Ø 15 cm / 6"	16215
	Ø 18 cm / 7.1"	16218
	Ø 20 cm / 8"	16220
	Ø 25 cm / 10"	16225
	Ø 30 cm / 12"	16230
	Threaded brush Perlon with M10 thread 16 mm inner hole diameter Ø 25 cm	15725
	Star Perlon Trimming thickness mm / 0.05" Ø 15 cm / 6"	2019
	Ø 20 cm / 8"	2752
	Ø 25 cm / 10"	2755
	Ø 35 cm / 13.8"	2018
	Star Perlon 2 mm / 0.08" bristles Ø 40 cm / 15.7"	8140
	Mini Hole Star HT Inner Ø 1 cm / 0.4" temperature resistant up to 250°C Ø 15 cm / 6"	19715
	Ø 20 cm / 8"	19720

Accessories		Article no.
	Mini Hole Star, HT 6 mm / 0.24" inner hole diameter temperature resistant up to 250 °C Ø 7 cm / 2.8"	15907
	Ø 10 cm / 4"	15910
	Ø 13 cm / 5.1"	15913
	Ø 15 cm / 6"	15915
	Ø 20 cm / 8"	15920
	Star Set HT · 2 Stars, HT, Ø 15 cm / 6" · 4 Stars, HT, Ø 20 cm / 8" · 2 Stars, HT, Ø 25 cm / 10"	3100
	Threaded Brush Perlon 2 mm / 0.08" 4 layers thread M10 deflector ball Ø 25 cm / 10"	4421
	Threaded Brush Perlon 2 layers M10 thread Ø 15 cm / 6"	18715
	Ø 18 cm / 7.1"	18718
	Ø 20 cm / 8"	18720
	Ø 25 cm / 10"	18725
	Ø 30 cm / 12"	18730
	Ø 35 cm / 13.8"	18735
	Ø 40 cm / 15.7"	18740
	Ø 50 cm / 20"	18750
	Ø 60 cm / 23.6"	18760
	Threaded Brush, HT 2 layers with M10 thread temperature resistant up to 250°C Ø 15 cm / 6"	19815
	Ø 18 cm / 7.1"	19818
	Ø 20 cm / 8"	19820
	Ø 25 cm / 10"	19825
	Threaded Brush, HT with guide ball and M5 thread temperature resistant up to 250°C Ø 7 cm / 2.8"	14607
	Ø 10 cm / 4"	14610
	Ø 13 cm / 5.2"	14613
	Ø 15 cm / 6"	14615
	Ø 20 cm / 8"	14620
	Brush Head Perlon with M10 thread Semicircular shape enables very good guidance in the tube for Rotary Viper M10 Ø 8 cm / 3.1"	7146
	Ø 10 cm / 4"	7147
	Ø 12.5 cm / 5"	1458
	Ø 18 cm / 7.1'	1466
	Ø 25 cm / 10"	7102

Accessories		Article no.
	Threaded Brush Perlon Trimming 2.0 mm / 0.08" with thread M10 Ø 20 cm / 8" 4 layers	4427
	Ø 35 cm / 13.8"	4424
	Threaded Brush Perlon Trimming 1.2 mm / 0.05" 2 layers with thread M10 Ø 20 cm / 8"	4332
	Ø 25 cm / 10"	3564
	Ø 30 cm / 12"	3500
	Threaded Brush Set Perlon Ø 20 - 35 cm / 8" - 13.8", with M10 thread 1 x Ø 20 cm / 8", 2 layers 1.2 mm 1 x Ø 25 cm / 10", 2 layers 1.2 mm 1 x Ø 30 cm / 12", 2 layers 1.2 mm 1 x Ø 35 cm / 13.8", 3 layers 2 mm	5529
	Deflection Spiral M10 made of stainless steel with internal and external thread, ideal for tight bends, for GRP rod Ø 6 mm and sweeping witch, also for push head adapter and mini push head	8638
	Deflector M 5 ideal for tight bends for mounting the mini hole stars or tube brushes M5	3838
	Guidance End Ball with M5 threaded pin for the GRP rod Ø 4.5 mm for fastening the PEK mini hole stars	8063
	Mini Push Head Aluminium Ideal for tight bends for mounting mini hole stars on the GRP rod Ø 6 mm or on the sweeping witch	7900
	GRP Rod 15 m long Ø 4.5 mm with 1 stainless steel end piece M5, spare rod for viper S	9703
	GRP Rod with 1 stainless steel end piece M10 spare rod for viper M Ø 7 mm 15 m	7015
	Ø 7 mm 20 m	7020
	GRP Rod with stainless steel end piece M10 on both sides replacement rod for viper L Ø 9 mm 15 m	9015
	GRP Rod Ø 9 mm 20 m	9020
	GRP Rod Ø 7 mm 3 m ball with M 10 screw	3211
	GRP Rod with 2 stainless steel end pieces and rubber end ball and M10 thread Ø 7 mm 5 m	3210
	Ø 9 mm 4 m	7363
	Ø 9 mm 5 m	1464
	Ø 9 mm 6 m	1124
	Ø 9 mm 8 m	1718
	Ø 11 mm 12 m	103
	GRP Rod with 2 stainless steel end pieces and rubber end ball and M10 thread Ø 11 mm 10 m	102
	GRP Rod Repair Kit with stainless steel end piece with 2 M4 cross holes, 2 grub screws and allen wrench Ø 4.5 mm	3687
	GRP Rod Repair Kit with stainless steel end piece with 2 M4 cross holes, 2 grub screws and allen wrench Ø 6 mm	3686
	Ø 7 mm	3696
	Ø 9 mm	3690
	Ø 11 mm	3691

Accessories		Article no.
	Steel Rod Type B 3 x Ø 3.8 mm, 3 m long with 2 brass end pieces with M10 internal thread	2731
	Steel Rod Type B 3 x Ø 3.8 mm, 5 m long with 2 brass end pieces with M10 internal thread	2732
	Steel Rods Type B 3 x Ø 3.8 mm, 5 m long, complete set with brass end section with M10 internal thread, alumi- nium end hand ball and large stainless steel push head for holding stars	5582
	Steel Rod Type D 3 x Ø 4.5 mm, 3 m long Extra hard, for intensive sweeping and burnout work, 2 brass end pieces with M10 internal thread	2834
	Steel Rod Type D 3 x Ø 4.5 mm, 6 m long Extra hard, for intensive sweeping and burnout work, 2 brass end pieces with M10 internal thread	2866
	Quick Change Star Holder Ø 28 mm for GRP rods Ø 7 – 11 mm for holding stars, one single movement opens the quick change star holder	9539
	Star Holder Ø 28 mm for holding stars for GRP rods Ø 7 - 11 mm and steel rods	7979
	Stainless Steel Star Holder Ø 28 mm for holding stars for steel rods and GRP rods Ø 7 - 11 mm and steel rods with aluminium cone stainless steel cap and stainless steel screw M10	5280
	Star Holder Ø 16 mm for holding stars for GRP rods Ø 7 – 11 mm and steel rods	10066
	Aluminium End Ball with M10 thread	1448
	Stainless Steel Rod Quick Connector with double-sided thread M10 with 17 mm wrench size, with union nut and anti-rotation lock via square spigot	1409
	Brass Rod Connector with double-sided thread M10 for connecting several GRP rods	1454
	Steel Chisel with M10 thread	1457
	Stainless Steel Roller Opener with M10 thread	1455
	Harpoon with M10 thread and barb	1459
	Sealing Element, round without hole for cleaning tasks Height 15 cm Ø 11 - 15 cm	8041
	Sealing Element Square with hole, for cleaning tasks Height 15 cm / hole Ø 4 cm 12 x 12 cm / 19 x 19 cm	40103
	110 x 230 mm / 190 x 310 mm 150 mm high, 40 mm hole	50666
	Wöhler Sealing Element for sealing fireplace doors or similar dimensions slotted with hole 20 x 30 cm Height 11.5 cm 18.5 x 22.5 cm / 27.5 x 34.5 cm	3430
	14x20 cm/12x18 cm Height 8.5 cm 13.5 x 19.5 cm / 17.5 x 23.5 cm	50000
	Wöhler Sealing Element 100 - 150 for sealing pipe connections slotted with hole Height 12.5 cm Ø 13 - 18 cm	54668
	Wöhler Soot Door Sealing for openings of 95 - 190 mm Ø and from 95 x 95 mm to 190 x 290 mm dust-free cleaning thanks to vacuum cleaner connection and feed-through for the rotary viper	3380
	Wöhler Sealing Elements Set to seal chimney doors 14 x 20 cm or similar measurements as well as pipe connections 100 – 150 mm or 150 – 200 mm	3708
	Sealing Element Set Round for cleaning tasks For sealing during the cleaning of air ducts Contains 4 sealing elements (without hole), diameters from Ø 110 mm to Ø 330 mm	7522

SF 300 Dust Collector

Cleaning of ventilation systems up to Ø 300 mm








- Applications**
- Simple and effective cleaning of ventilation lines up to Ø 300 mm
 - The Dust Collector creates strong negative pressure to extract dirt and dust particles directly during the cleaning process

- Features**
- Can be used in vertical and horizontal position
 - Easy to transport
 - Simple set up
 - Simultaneous connection of 2 hoses possible
 - Hose extension for hard to reach vents

Technical Data		
Suction Power	approx. 1,000 m³/h air (with hose Ø 200 mm)	
Motor	Type	EMG Single phase Asynchronous-motor ECS 7IG 2 – A1AA
	Pressure	230 V
	Frequency	50 Hz
	Nominal power	0.55 kW
Operating Environment	Protection class	IP 54
	Insulation class	F
Operating Temperature	-35...40 °C	
Vacuum blower	Dimension	90 x 41 x 46 cm
	Weight	29 kg

SF 300 Dust Collector
Scope of delivery: SF 300 Dust Collector and 5 m long hose Ø 200 mm with integrated filter incl. adaptor
Article no. 6190

Accessories		Article no.
	Replacement Hose for SF 300 5 m long Ø 160 mm	6192
	Ø 200 mm	6191
	Adapter for SF 300 Dust Collector Ø 160 mm / Ø 100 mm	6198
	Ø 200 mm / Ø 160 mm	6199
	Hose Bag for SF 300 Dust Collector for holding one hose Ø 200 mm and one Ø 160 mm, 5 m long	6193
	Prefilter (filter class M5) for SF 300 Dust Collector	6194
	Microfilter (filter class F7) for SF 300 Dust Collector	6195

WÖHLER
ACADEMY

CLEANING

Cleaning of a ventilation system / air duct with compressed air

Regular inspection and cleaning of ventilation systems ensure that the operator's ventilation system is in perfect hygienic and technical condition and can also contribute to energy savings. Contamination of the ventilation ducts leads to air volume deviations, which affects the indoor climate and therefore the indoor air quality.

Scan now!



wohler.co.uk/
Cleaning



Wöhler Compressed Air Cleaning

Cleaning of square and round air ducts



Applications

- Cleaning square and round air ducts

Features

- Easy handling of the compressed air / water
- Water reel thanks to the coupling bracket
- Suitable for small and large cross-sections
- Can be extended using hose reel

Technical Data

Digital metre counting	Measurement unit	Metres or feet (m or ft)
	Resolution	0.1
	Battery	Long-life lithium battery
Requirements for a compressor to be connected	Pressure	min. 5 bar
	Output power	25 m³/h

Wöhler DH 420 Pneumatic Viper

10 m, compressed air hose

Scope of delivery: GRP hose incl. stop value and compressor connection

Article no. 7580

Wöhler Compressed Air Cleaning

Standard Set

Scope of delivery: compressed air hose 7 m incl. stop value and Wöhler backwards rotating helicopter nozzle, in a plastic case

Article no. 7560

Wöhler Compressed Air Cleaning

Professional Set

Scope of delivery: Wöhler DH 420 Pneumatic Viper with 10 m compressed air GRP hose incl. stop valve and compressor connection, compressed air hose reel with 20 m hose, Wöhler compressed air whip with 7 ends 50 cm long, Wöhler backwards rotating helicopter nozzle, guidance roller ball and XXL-alu case

Article no. 7570

Accessories

		Article no.
	Hose Reel (Air/Water) 20 m hose - compressed air cleaning incl. 1.5 m connecting hose and adapter plug	7565
	Wöhler Roller Guide Ball Compressed air cleaning for guiding the Wöhler DH 420 Pneumatic Viper in angular shaped ventilation pipes, Ø 95 mm	7552
	Wöhler helicopter nozzle backwards rotating for DH 420 suitable for compressed air cleaning, combines brushes and nozzle effect to loosen stubborn dirt in small pipes, easy guidance especially in vertical air ducts thanks to the recoil principle	7556
	forwards rotating for DH 420 suitable for compressed air cleaning, combines brushes and nozzle effect to loosen stubborn dirt in small pipes, easy guidance especially in vertical air ducts thanks to the recoil principle	7557
	Service Bag Helicopter Nozzles 2 strings 20 cm long, 1 grub screw and 1 angled screwdriver SK 2.5 ATTENTION: Only suitable for helicopter nozzles with plastic head!	7578
	Wöhler Compressed Air Whip with 7 ends for DH 420 inside Ø 2.0 mm, 50 cm long, particular suitable for bigger pipe diameters	7562
	Sealing Element Set Round for cleaning tasks For sealing during the cleaning of air ducts Contains 4 sealing elements (without hole), diameters from Ø 110 mm to Ø 330 mm	7522
	Sealing Element Set Rectangular 5 x120 x 120 to 390 x 390 mm (without hole)	7523
	Wöhler Soot Door Sealing for openings of 95 - 190 mm Ø and from 95 x 95 mm to 190 x 290 mm; dust-free cleaning thanks to vacuum cleaner connection and feed-through for the rotary viper	3380
	Sealing Set Ventilation sealing bladder size 3 for Ø 100 – 250 mm and size 5 for Ø 200 – 400 mm, with release valve	7506
	Sealing Bladder for Wöhler DP 700 with 5 clamps Size 3 Ø 100 - 250 mm	3314
	Size 5 Ø 200 - 400 mm	3316
	Size 10 Ø 315 - 630 mm	3317
	Aluminium Pump Master-Blaster for test sets, gas pipes and sealing bubbles	53817

Wöhler online shop

Discover all the details about the product and much more. Plus, ordering is easy!

wohler.co.uk/P_114





INTERNATIONAL OPERATING, INDEPENDENT, GERMAN FAMILY-OWNED COMPANY

For over 90 years, we have been a technically orientated, internationally operating family business with more than 260 employees worldwide.

We are a leading manufacturer of measurement technology, inspection technology and cleaning technology with headquarters in Bad Wünnenberg, Germany.

Scan the QR code and find out more about our corporate culture, how we are committed to sustainability and how we act as an employer.



[wohler.co.uk/
company](https://www.wohler.co.uk/company)

WÖHLER

WOHLER UK LIMITED

G1 Lincoln House · Lincoln Way · Sherburn in Elmet · LS25 6PJ

Phone: 01977 80 60 40 · **E-Mail:** info@wohler.co.uk