

Wöhler VIS 250 Inspection Camera



Technical data

Monitor	Dimensions housing	176 x 114 x 32 mm
	TFT-display	7" / 16:9 format
	Video out	RCA signal
	Weight	400 g
	Power supply	Space for 2 rechargeable batteries, each 12 V or via power pack
	Battery operating time	Max. 2 rechargeable batteries, each 120 mins. = 4 h (battery status in display)
Wöhler miniature camera head Ø 26	Type	1/3" COLOR CMOS
	Resolution	420 lines
	Pixels	768 x 576 (PAL) 656 x 492 (NTSC)
	Light sensitivity	0,5 Lux
	Lens	f = 2,3 mm, F = 2,5
	Viewing angle	145°
	Light source	12 white LEDs
	Degree of protection	Waterproof to IP 68
	Dimensions	Ø 26 x 38 mm
	Weight	240 g
	Operation temperature	0...40 °C, RH 95 % MAX
	Storage temperature	-20...50 °C, RH 95 % MAX
	Transmitter frequency	9,2 kHz
	Distance measurement	Electronic meter counter
Plastic case	Dimensions	51 x 43 x 17 cm
	Weight	7 kg
Memory (Wöhler VIS 250)	Recording	4 GB SD card (5 h recording capacity)
	Interface	Mini USB port

WÖHLER

Wöhler Technik GmbH
Headquarters Germany

Wöhler-Platz 1 · 33181 Bad Wünnenberg

www.woehler-international.com